



SMALL LED/LCD

Hantarex International Limited
34 Salisbury Street
London, NW8 8QE
Tel: 0044 (0) 208 778 1414
e-Mail: sales@hantarex.com

DSM12.1WGF

12.1" Active Matrix With Glass Front/ Metal Case

DSM12.1WGF

Panel Type	12.1" (4:3) LCD Monitor with Glass Front
Case Type	Metal
Maximum Resolution	800 (H) x 600 (V)
Active Display Area	246.0 (H) x 184.5 (V)
Pixel Pitch	0.3075 (H) x 0.3075 (V) mm
Bezel Thickness	28.25 mm
Contrast Ratio	450 : 1 Ratio
Brightness	330 cd/ m ²
Response Time	10 - 35 ms
Viewing Angle	U/D: 50° / 60°, L/R: 70° / 70°
Display Colours	16.7 M
Video Synchronization	Yes
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V) Max. 800 x 600
Adjustable Colour Temperature	Yes
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	4 : 3 Ratio
VGA Auto Frequency correction	No
Speaker	N/A
Number of Speakers	N/A
Sound Demodulation	N/A
Mute	N/A
Work Humidity	20 % - 70 %
Work Temperature	-10 to 50 °C
Volume +/- Power On/Off	Power ON/OFF Only



POWER

Power Supply	12V, 2 amps
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	< 24W in "ON"

IN/OUT INTERFACE

Video Interface	VGA In x 1 BNC In x 1, BNC Out x 1
Audio Interface	None
Power Interface	AC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	ROHS-2, CE, FCC, C-Tick, E13, WEEE
Vesa Standard Mount	75 x 75 mm
Stand Type	Picture
Colour	Black
Button Position	Right Hand side
Packing Dimension	390 (W) x 350 (H) x 121 (D) mm
NET Weight	2.1 Kgs
GROSS Weight	2.9 Kgs

OSD CONTROLS

Contrast, Brightness, Language, Sharpness, Saturation, Timer, H-Position, V-Position,





OSD LANGUAGE

English, French, German, Spanish, Italian, Chinese

ACCESSORIES

Power Supply, VGA Cable, Picture Frame Stand, User Manual

Hantarex International Limited
34 Salisbury Street
London, NW8 8QE
Tel: 0044 (0) 208 778 1414
e-Mail: sales@hantarex.com



Hantarex International Limited
34 Salisbury Street
London, NW8 8QE
Tel: 0044 (0) 208 778 1414
e-Mail: sales@hantarex.com

