



SMALL LED/LCD

Hantarex International Limited
34 Salisbury Street
London, NW8 8QE
Tel: 0044 (0) 208 778 1414
e-Mail: sales@hantarex.com

DSM5WGF

5" Active Matrix with Metal Case Glass Fronted

DSM5WGF

Panel Type	5" (4:3) LED Monitor with Glass Front
Case Type	Metal
Maximum Resolution	640 (H) x 480 (V)
Active Display Area	101.568 x 76.176 (V) mm
Pixel Pitch	0.0529 (H) x 0.1587 (V) mm
Bezel Thickness	24.21 mm
Contrast Ratio	500 : 1 Ratio
Brightness	200 cd/ m ²
Response Time	10ms - 15ms
Viewing Angle	U/D: 50° / 70°, L/R: 70° / 70°
Display Colours	16.7 M
Video Synchronization	Yes
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V) Max. 640 x 480
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	4 : 3 Ratio
VGA Auto Frequency correction	Yes
Speaker	No
Number of Speakers	No
Sound Demodulation	No
Mute	No
Work Humidity	20 % - 70 %
Work Temperature	- 10 to 50 °C
Volume +/- Power On/Off	Yes



POWER

Power Supply	12VDC, 1amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	< 12W in "ON"

IN/OUT INTERFACE

Video Interface	BNC Input x 2
Audio Interface	None
Power Interface	AC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	ROHS-2, CE, FCC, C-Tick, E13, WEEE, Energy Star.
Vesa Standard Mount	44 x 24 mm (in base)
Stand Type	Multi Functional Desktop/ Wall mount
Colour	Black
Packing Dimension	270 (W) x 210 (H) x 120 (D) mm
NET Weight	0.8 Kg
GROSS Weight	1.1 Kg

OSD CONTROLS

Contrast, Brightness, Language, Colour, Tint, Rotation Up/Down, Input source AV1, AV2, Reset

OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish, Portuguese

ACCESSORIES

Power Supply, Remote Control, Multi Functional Bracket Desktop/ Wall Mount, User Manual.

Hantarex International Limited
34 Salisbury Street
London, NW8 8QE
Tel: 0044 (0) 208 778 1414
e-Mail: sales@hantarex.com

