

Hantarex International Limited 34 Salisbury Street London, NW8 8QE Tel: 0044 (0) 208 778 1414 e-Mail: sales@hantarex.com

65" INTERACTIVE TOUCH DISPLAY



"The etched glass not only defuses the light, increasing readability but also makes touch movements smoother; essential when there are six touch points"

EASY ACCESS FRONT CONTROLS AND PORTS



Connect your laptop directly to the Interactive Touch Display with no fuss.

EASY TO MOVE THANKS TO OPTIONAL TROLLEY STAND



Either install onto a classroom wall or invest in a fully portable trolley stand - allowing for improved diversity. Use in any classroom you like or even the assembly hall for playing DVDs.

YOUR FINGER BECOMES THE MOUSE



Use your finger, stylus or anything else as your cursor. Also supports multi-touch, much like a smart phone, creating a whole new opportunity for group leaning and interaction.

MULTITUDE OF ADVANTAGES OVER PROJECTORS



Sharper image and greater contrast provide drastically superior readability and doesn't take its toll on your eyes. Also designed to last 16 times longer than most projector lamps and doesn't create annoying shadows.

RUNS FROM INTERNAL PC OR LAPTOP



You can either run the Interactive Touch Display directly from your laptop or invest in an internal PC.

ENVIRONMENTALLY FRIENDLY LED BACKLIGHT



LED backlights offer improved brightness, contrast, lifespan and power consumption. Unlike other forms of light this technology is mercury free; making it even more eco-friendly.







Begin by wheeling your Interactive Whiteboard where ever you want to use it.

Connect to your laptop via USB and HDMI cables (or run from internal PC).

Away you go! Open the door to interactive group learning.

Screen Size	65 inch
Display Area (WxH mm)	1428x803
Aspect Ratio	16:9
Brightness (cd/m2)	500
Contrast	5,000:1
Viewing Angle	178°
Display Resolution	1920x1080
Display Life	More than 60,000 hours
Video	PAL/SECAM
Speakers	2x15W
Touch Technology	Infrared six-point touch
Minimum Touch Object	≥5mm
Response Time	≤5ms
Positioning Accuracy	±2mm
Interpolated Resolution	32768x32768
Touch Interface	USB
Operating System	6-Point - Android, Linux, Windows XP/2003/Vista/7/ 8
	1-Point - Mac
Touch Times	Unlimited
Inputs (front)	USB (touch) x 1, USB (PC) x 1, VGA x 1, HDMI x 1
Inputs (side)	AV/Audio x 1, S-Video/Audio x 1, VGA/Audio x 1, YPbPr/YCbCr, TV x 1, HDMI, Multi-Media USB x 1, Touch USB (Type B) x 1
Outputs	AV/Audio x 1, Coaxial Digital Audio x 1
Power Supply	AC 110-240V, 50Hz/60Hz
Power Consumption	≤180W
Power Consumption (standby)	≤0.5W
VESA Holes (WxH mm)	600x400
Unit Size (WxHxD mm)	1512.4x902.4x74.7
Package Size (WxHxD mm)	1735x1165x315
Net Weight (kg)	67
Gross Weight (kg)	77
Working Temperature	0°C
Storage Temperature	5°C
Working Humidity	10%
Storage Humidity	35%
Accessories	Remote Control x 1, HDMI Cable 1.5M x 1, USB Extension Cable 1.5M x 1, Power Cord x 1, AAA Battery x 2